



Revisions:

Test gerilimi	27.0 V.	
Q ₁	1.5 l/dk	Q ₂ 0 l/dk
P ₁	1.8 Atu	P ₂ 2.4 Atu
I ₁	1.60 A	I ₂ 1.40 A

Ref.standart :9.93612 Fiat Şartnamesi

© Critical Measure

GENEL TOLERANS TABLOSU									
DIN 2768									
TOLERANS SINIFI	0,5	3	6	30	120	400	1000	2000	
	3	6	30	120	400	1000	2000	4000	
f	Çok Hassas	$\pm 0,05$	$\pm 0,05$	$\pm 0,1$	$\pm 0,15$	$\pm 0,2$	$\pm 0,3$	$\pm 0,5$	-
m	Hassas	$\pm 0,1$	$\pm 0,1$	$\pm 0,2$	$\pm 0,3$	$\pm 0,5$	$\pm 0,8$	$\pm 1,2$	± 2
c	Kaba	$\pm 0,2$	$\pm 0,3$	$\pm 0,5$	$\pm 0,8$	$\pm 1,2$	± 2	± 3	± 4
v	Çok Kaba	-	$\pm 0,5$	± 1	$\pm 1,5$	$\pm 2,5$	± 4	± 6	± 8

Drawn by	Date	Name - Surname	Signature
Approved by	17.02.2014	Gizem GÖKÇEK	
Scale	Part definition	Afşin KANDEMİR	
1/1	MES DALGIÇ POMPA 24V TEK ÇIKIŞ		

AFK Otomotiv
Elektromekanik, Plastik
İmalat San. Tic. Ltd. Şti.

Drawing 107AA028

Material -

Non-defined Tolerances (f) Çok Hassas