



Test gerilimi	13.5 V.	
Q ₁	1.5 l/dk	Q ₂ 0 l/dk
P ₁	1.5 bar	P ₂ 2.3 bar
I ₁	3.40 A	I ₂ 3.0 A

Ref.standart :9.93612 Fiat Şartnamesi

© Critical Measure

GENEL TOLERANS TABLOSU DIN 2768										
TOLERANS SINIFI	0,5 3	3 6	6 30	30 120	120 400	400 1000	1000 2000	2000 4000		
f	Çok Hassas	±0,05	±0,05	±0,1	±0,15	±0,2	±0,3	±0,5	-	
m	Hassas	±0,1	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2	
c	Kaba	±0,2	±0,3	±0,5	±0,8	±1,2	±2	±3	±4	
v	Çok Kaba	-	±0,5	±1	±1,5	±2,5	±4	±6	±8	

Drawn by	12.05.2006	Arzu ÇAVDAR
Approved by	12.05.2006	Afşin KANDEMİR
Scale	Part definition	
	1:1,5	

Date	12.05.2006	Name-Surname	Arzu ÇAVDAR	Signature	
	12.05.2006		Afşin KANDEMİR		
Part definition					
CAM YIKAMA POMPASI 12V ÇİFT ÇIKIŞLI					

AFK Otomotiv
Elektromekanik, Plastik
İmalat San. Tic. Ltd. Sti.

Drawing **107AA009 R0**

Material -

Non -defined Tolerans (f) Çok hassas

Revisions: