



Flow Rate

>0,85 lt / min.with P:2 bar and attached nozzle with 2x0,8 mm holes

Opening Pressure

<0,7 bar , attached nozzle with 2x0,8 mm holes

Closing Pressure

>0,1 bar measured after T:50 s

Storage Temp

-40°C - +100°C

Operating Temp

-30°C - +90°C

Revisions:

GENEL TOLERANS TABLOSU DIN 2768									
TOLERANS SINIFI	0,5 3	3 6	6 30	30 120	120 400	400 1000	1000 2000	2000 4000	
f	Çok Hassas	±0,05	±0,05	±0,1	±0,15	±0,2	±0,3	±0,5	-
m	Hassas	±0,1	±0,1	±0,2	±0,3	±0,5	±0,8	±1,2	±2
c	Kaba	±0,2	±0,3	±0,5	±0,8	±1,2	±2	±3	±4
v	Çok Kaba	-	±0,5	±1	±1,5	±2,5	±4	±6	±8

No	Part Definition	AFK S.C.	Material	Quantity
		Date	Name-Surname	Signature
	Drawn by	22.12.2005	Arzu ÇAVDAR	
	Approved by	22.12.2005	Afşin KANDEMİR	
	Scale	Part definition		
	2:1	ÇEKVALF / SİYAH		
		Drawing 122AD001 R0		
		Material POM		
		Non -defined Tolerans (c) Kaba		

**AFK Otomotiv**  
Elektromekanik, Plastik  
İmalat San. Tic. Ltd. Sti.